

FORESTRY MULCHERS FOR SKID STEERS

UML/SSL/BL

Forestry mulcher with Bite Limiter rotor system.

Robust and compact, the UML/SSL/BL is renowned for its ergonomic design that guarantees excellent visibility for the operator during various situations. This machine can be equipped with two types of hydraulic motors: the VT motor with automatic variable

displacement and increased torque and the SONIC motor, a FAE exclusive that optimizes performance and can be easily managed using the dedicated FAE App for smartphone.



Sonic System



75-135 hp



Ø 8 in max



Rotor Bite Limiter



Sonic System is a new automatic intelligent system that manages the hydraulic transmission. It makes the mulching machine to perform at the maximum capacity in all conditions (UML/SSL/BL/SONIC)



Reinforced frames
Provides extra protection from the power of the carrier

STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/BL/VT)	110cc variable torque hydraulic piston motor (32-53 gpm) (UML/SSL/BL/SONIC)
Adjustable skids	Working pressure control gauge
Safety and anticavitation valve	Guard frame
Enclosed / anti dust machine body	Dual row protection chains
Motor enclosed in the frame	Welded counterblades
Timing belt transmission	Rotor Bite Limiter
Hydraulic hoses	Sonic System (UML/SSL/BL/SONIC)
Rear deflector	Adaptor wiring

OPTIONS


Customized setting hydraulic motor (UML/SSL/BL/VT)	Universal cabin roof hydraulic oil cooler kit
Oil cooler kit	

Case drain required

MODEL	UML/SSL/BL/VT-150	UML/SSL/BL/VT-175	UML/SSL/BL/SONIC-150	UML/SSL/BL/SONIC-175
Power (hp)	75-135	75-135	75-135	75-135
Flow rate (gal/min)	30-53	30-53	30-53	30-53
Pressure (PSI)	2900-5080	2900-5080	2900-5080	2900-5080
Working width (in)	62	72	62	72
Total width (in)	74	83	74	83
Weight (lbs)	2866	3086	2866	3086
Rotor diameter (in)	17.3	17.3	17.3	17.3
Max shredding diameter (in)	8	8	8	8
No. blades type BL + C/3/SS	24+2	30+2	24+2	30+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

MAIN OPTIONS



Customized setting hydraulic motor

ROTOR TYPE BL



BLADE BL
(standard)



TOOTH C/3/SS
(side scraper)